



City of Rohnert Park  
Public Works Department

DATE: March 12, 2019  
TO: ALL PLANHOLDERS  
SUBJECT: City of Rohnert Park  
Callinan Sports Center Water Damage Repair Project  
Project No. 2018-42  
NO. OF PAGES: 2

---

## **ADDENDUM NO. 2**

This package provides an addendum to the Project Contract Documents. This Addendum shall become part of the Contract and all provisions of the Contract shall apply thereto.

Bidders shall acknowledge receipt of this Addendum by signing the acknowledgement located in the Bid Proposal documents, under "Addendum Acknowledgement." Failure to do so may cause your bid to become non-responsive and subject to rejection.

### **1. CONTRACT DOCUMENTS/SPECIFICATIONS CHANGE AS FOLLOWS:**

#### **ATTACHMENT A SCOPE OF WORK**

##### **Southern Hallway**

Replace second bullet as follows: Replace flooring with Carthage Legacy 26 20 oz Infinity Modular 24x24 modular tiles with Manufacture's recommended adhesive (see Technical Specification) or equal 1,403 SF

#### **PART 4 – TECHNICAL SPECIFICATIONS**

Replace new Pages 4-5 for carpet

Addendum No. 2 approved by:

  
Terrie Zwillinger, Project Manager

3-12-19  
Date

**PHYSICAL CONSTRUCTION:**

---

CONSTRUCTION:	Graphic Loop Pile (Non-Ortho Phthalate Construction)
FACE FIBER:	Invista Antron Legacy Type 6,6 Four Hole, Hollow Filament Nylon, with Permanent Stain and Bleach Protection, Static Control, and Duratech Soil Resistant Treatment, and a Fiber Modification Ratio of <1.5
DYE METHOD:	Solution / Yarn
GAUGE:	1/10
STITCHES PER INCH:	10
PILE THICKNESS:	.096 Inches
TUFTED YARN WEIGHT:	20 Ounces Per Square Yard
DENSITY:	Average Density =7,500; Weight Density = 150,000
PRIMARY BACKING:	100% Synthetic
SECONDARY BACKING:	Infinity Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	24" X 24" Modular Tiles
INSTALLATION METHOD:	Monolithic

**ENVIRONMENTAL:**

---

RECYCLED CONTENT:	Contains Pre-Consumer Recycled Content*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Gold
CRI GREEN LABEL PLUS ID:	GLP7616
3 <sup>rd</sup> Party Certified Product Specific Type III EPD	

**WARRANTIES:**

---

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Delamination, Tuft Bind, Unraveling, and Static Protection
BLEACH RESISTANT WARRANTY:	ColorSafe with 15 Year Limited Warranty Against Color Loss from Bleach Spills
STAIN RESISTANT WARRANTY:	XGUARD with 15 Year Limited Warranty Against Staining

**PRODUCT TESTING:**

---

RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILTY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

**RECOMMENDED ADHESIVE:**

---

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

\* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.